

PERMAPRESS BOILING PANS - RECTANGULAR

- Low-maintenance, closed PERMAPRESS system
- Temperature of the food adjusted manually
- Knob to switch from initial cooking level to simmering level
- double-walled lid, spring-released and balanced with all-round seal made of temperature-resistant elastomer
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 50 (2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Filling level marking with 25-litre graduations on FER 301 and FER 401, 50-litre graduations on FER 501
- Continuous cooking mode
- Contactor as a standard



	FER 301	FER 401	FER 501
Overall dimensions, W x D x H in mm	1600 x 850 x 900	2100 x 850 x 900	2400 x 850 x 900
Weight in kg	256	322	425
Electrical connection in kW 400 V 3N 50/60 Hz	36.6	42.6	54.6
Usable capacity in litres	294	422	500
Dimensions of inner pan, W x D x H in mm	1150 x 660 x 435	1650 x 660 x 435	1955 x 660 x 435
Capacity of inserts GN 1/1, 200 mm	8 Units	12 Units	14 Units
Boiling time, determined to DIN 18855, in minutes	43	48	55

STANDARD ACCESSORY

1 strainer	●	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●	●

ACCESSORIES

ZUB 679 Container support	○		
ZUB 680 Container support		○	
ZUB 681 Container support			○

○ = Optional (price on request)

