

PERMAPRESS FAST BOILING PANS - RECTANGULAR

- Low-maintenance, closed PERMAPRESS system
- Temperature of the food adjusted manually
- Knob to switch from initial cooking level to simmering level
- Double-walled lid, spring-released and balanced with all-round seal made of temperature-resistant elastomer
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 50 (2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Filling level marking with 10-litre graduations on FER 151, 25-litre graduations on FER 251
- Continuous cooking mode
- Contactor as a standard



	FER 151	FER 251
Overall dimensions, W x D x H in mm	1100 x 850 x 900	1400 x 850 x 900
Weight in kg	183	220
Electrical connection in kW 400 V 3N 50 / 60 Hz	24.6	30.6
Usable capacity in litres	158	253
Dimensions of inner pan W x D x H in mm	620 x 660 x 435	990 x 660 x 435
Capacity of inserts GN 1/1, 200 mm	4 Units	6 Units
Boiling time, determined to DIN 18855, in minutes	35	45
Fast boiling pan according to DIN 18855	●	●

STANDARD ACCESSORY

1 strainer	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●

ACCESSORIES

ZUB 677 Container support	○	
ZUB 678 Container support		○

○ = Optional (price on request)

