


PERMAPRESS TILTING FAST BOILING PANS

- Innovative  touch panel control
- Low-maintenance, closed PERMAPRESS system
- Electronic temperature controls with target and actual temperature display and 3 fast activation settings each for the cooking time and temperature
- Double-walled lid, spring-released, balanced
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 40 (1 1/2")
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Filling level marking with 5-litre graduations
- Bottom unit as a H2 hygienic model
- Fast boiling pan to DIN 18855
- Cleaning-friendly hygiene axles
- Motorised tilting
- Built-in contactors



	FEK 060	FEK 100	FEK 150
Overall dimensions, W x D x H in mm	1000 x 850 x 900	1100 x 850 x 900	1300 x 850 x 900
Weight in kg	170	192	212
Electrical connection in kW 400 V 3N 50/60 Hz	12.6	18.6	23.1
Usable capacity in litres	63.5	109	155
Inner pan diameter in mm	484	584	697
Inner pan height in mm	410	470	470
Boiling time, determined to DIN 18855, in minutes	25	31,5	36
Fast boiling pan according to DIN 18855	●	●	●


STANDARD ACCESSORY

1 strainer	●	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●	●




TOP OPTION

VAR 320 Volume-regulated water intake device (cold, warm and mixed water)

- Water automatically filled to the exact litre
- Rapid selection of various filling quantities with a  touch panel
- Automatic filling process stop

	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
--	-----------------------	-----------------------	-----------------------

VAR 808 Core temperature probe

- Cooking to perfection
- Rapid selection of various temperatures with a  touch panel
- Save on energy through optimal cooking time

	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
--	-----------------------	-----------------------	-----------------------

ACCESSORIES

ZUB F47 Discharge strainer for 60-litre boiling pans	<input type="radio"/>		
ZUB F48 Discharge strainer for 100-litre boiling pans		<input type="radio"/>	
ZUB F49 Discharge strainer for 150-litre boiling pans			<input type="radio"/>
ZUB 320 1 pair of lifting hooks	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
ZUB 322 Support ring for inserts	<input type="radio"/>		
ZUB 323 Support ring for inserts		<input type="radio"/>	
ZUB 324 Support ring for inserts			<input type="radio"/>
Inserts, 8 mm perforation (up to 2 inserts per appliance)			
ZUB 382 1 insert, diameter 465 mm, height 150 mm	<input type="radio"/>		
ZUB 384 1 insert, diameter 565 mm, height 180 mm		<input type="radio"/>	
ZUB 389 1 insert, diameter 675 mm, divided, height 180 mm			<input type="radio"/>
Inserts, 2.5 mm perforation (up to 2 inserts per appliance)			
ZUB 392 1 insert, diameter 465 mm, height 150 mm	<input type="radio"/>		
ZUB 394 1 insert, diameter 565 mm, height 180 mm		<input type="radio"/>	
ZUB 399 1 insert, diameter 675 mm, divided, height 180 mm			<input type="radio"/>

○ = Optional (price on request)

Electric 