

GAS CAST-IRON TILTING BRATT PANS

- With a double-walled lid as a standard, spring-released, balanced
- Cleaning-friendly hygiene axles
- Motor tilting function with fast return
- Bottom unit as a H2 hygienic model
- Accurate pouring, pan emptied via integrated discharge spout



	FGP 600	FGP 900
Overall dimensions, W x D x H in mm	1100 x 850 x 900	1400 x 850 x 900
Weight in kg	217	265
Nominal heat load in kW natural gas E, 20 mbar	18	24
Electrical connection in kW 230 V 1N 50/60 Hz	0.3	0.3
Cast iron pan, W x D x H in mm	600 x 600 x 175	900 x 600 x 175
Maximum capacity in litres	69	103
Usable capacity in litres	53	80
Frying surface in m ²	0.3	0.47
Double-walled lid	●	●
Operation via control knob	●	●
Hygienic bottom structure H2	●	●
STANDARD ACCESSORY		
1 stainless-steel-clad safety gas tube	●	●
OPTION		
VAR 477 Swivel tap 3/4" for WW, radial excursion 300 mm, height 80/390 mm	○	○
ACCESSORIES		
ZUB 961 Swivel tap 3/4" for WW, radial excursion 300 mm, height 80 / 390 mm (assembly set)	○	○
ZUB 960 Swivel tap 1/2" for WW, radial excursion (assembly set)	○	○
ZUB 832 Safety gas tube 1/2", 600 mm for connection through the rear wall	○	○
Injector sets for different gas types	see page 69	see page 69

○ = Optional (price on request)

