


GAS PERMAPRESS FAST BOILING PANS

- Innovative  touch panel control
- Electronic temperature controls with set and actual temperature display and 3 fast activation settings each for the cooking time and temperature
- Double-walled lid, spring-released, balanced
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 40 (1 1/2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Filling level marking with 5-litre graduations
- Gas regulating valve, automatic ignition with high voltage ignition
- Ignition safeguard through monitored ionization
- Integrated gas connection and shut-off valve



	FGS 060	FGS 100	FGS 150
Overall dimensions, W × D × H in mm	800 × 850 × 900	900 × 850 × 900	1100 × 850 × 900
Weight in kg	132	153	180
Nominal heat load in kW natural gas E, 20 mbar	12.5	17	21
Electrical connection in kW 230 V 1N 50/60 Hz	0.05	0.05	0.05
Usable capacity in litres	63.5	109	155
Inner pan diameter in mm	484	584	697
Inner pan height in mm	410	470	470
Boiling time, determined to DIN 18855, in minutes	37.5	42.5	51
Fast boiling pan according to DIN 18855	●	●	●

STANDARD ACCESSORY

1 strainer	●	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●	●
1 stainless-steel-clad safety gas tube	●	●	●
ZUB 418 Fume vent without damper, with deflector (for installation beneath a cooker hood or ventilating ceiling)	separate position included in the price		




TOP OPTION

VAR 320 Volume-regulated water intake device (cold, warm and mixed water)

• Water automatically filled to the exact litre			
• Rapid selection of various filling quantities with a  touch panel			
• Automatic filling process stop	○	○	○

VAR 808 Core temperature probe

• Cooking to perfection			
• Rapid selection of various temperatures with a  touch panel			
• Save on energy through optimal cooking time	○	○	○

ACCESSORIES

ZUB 787 Double jacket for exhaust gas chimney	○	○	○
ZUB 320 1 pair of lifting hooks	○	○	○
ZUB 322 Support ring for inserts	○		
ZUB 323 Support ring for inserts		○	
ZUB 324 Support ring for inserts			○
Inserts, 8 mm perforation (up to 2 inserts per appliance)			
ZUB 382 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 384 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 389 1 insert, diameter 675 mm, divided, height 180 mm			○
ZUB 787 Double jacket for exhaust gas chimney			
ZUB 392 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 394 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 399 1 insert, diameter 675 mm, divided, height 180 mm			○
Injector sets for different gas types	see page 69	see page 69	see page 69

○ = Optional (price on request)

