



GAS RECTANGULAR FAST BOILING PANS – ADVANCED GAS TECHNOLOGY

- Innovative touch panel
- Gas blower technology for maximum effect and economy
- Electronic temperature controls with set and actual temperature display and 3 fast activation settings each for the cooking time and temperature
- Double-walled lid, spring-released and balanced with all-round seal made of temperature-resistant elastomer
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 50 (2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Filling level marking with 10-litre graduations on FLR 150, 25-litre graduations on FLR 250



	FLR 150	FLR 250
Overall dimensions, W x D x H in mm	1200 × 850 × 900	1500 × 850 × 900
Weight in kg	270	310
Nominal heat load in kW natural gas E, 20 mbar	27	36
Electrical connection in kW 230 V 1N 50/60 Hz	0.15	0.15
Usable capacity in litres	158	253
Dimensions of inner pan W x D x H in mm	620 × 660 × 435	990 × 660 × 435
Capacity of inserts GN 1/1, 200 mm	4 Units	6 Units
Fast boiling pan according to DIN 18855	●	●
Boiling time, determined to DIN 18855, in minutes	35	40

STANDARD ACCESSORY

1 strainer	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●
1 stainless-steel-clad safety gas tube	●	●



TOP OPTION

VAR 320 Volume-regulated water intake device (cold, warm and mixed water)

- Water automatically filled to the exact litre
- Rapid selection of various filling quantities with a touch panel
- Automatic filling process stop

○

○

VAR 808 Core temperature probe

- Cooking to perfection
- Rapid selection of various temperatures with a touch panel
- Save on energy through optimal cooking time

○

○

ACCESSORIES

ZUB 791 Double jacket for fume vent, for upgrading appliance	○	○
ZUB 677 Container support	○	
ZUB 678 Container support		○
Injector sets for different gas types	see page 69	see page 69

○ = Optional (price on request)

