


LOW-PRESSURE STEAM TILTING FAST BOILING PANS

- Innovative  touch panel control
- Electronic temperature controls with set and actual temperature display and 3 fast activation settings each for the cooking time and temperature
- Double-walled lid, spring-released, balanced
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 40 (1 1/2")
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Heating by direct steam supply, 0.3 – 0.5 bar gauge pressure
- Filling level marking with 5-litre graduations
- Cleaning-friendly hygiene axles
- Bottom unit as a H2 hygienic model
- Motor tilting function



	FNK 060	FNK 100	FNK 150
Overall dimensions, W x D x H in mm	1000 x 850 x 900	1100 x 850 x 900	1300 x 850 x 900
Weight in kg	164	178	189
Rated output in kW	20.0 at 32 kg/h	29.0 at 46 kg/h	35.0 at 56 kg/h
Electrical connection in kW 230 V 1N 50/60 Hz	0.25	0.25	0.25
Usable capacity in litres	63.5	109	155
Inner pan diameter in mm	484	584	697
Inner pan height in mm	410	470	470
Boiling time, determined to DIN 18855, in minutes (at 0.5 bar gauge pressure)	16	19	21.5
Fast boiling pan according to DIN 18855	●	●	●


STANDARD ACCESSORY

1 strainer	●	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●	●
1 stainless-steel-clad pressure hose for supply of low-pressure steam	●	●	●




TOP OPTION

VAR 320 Volume-regulated water intake device (cold, warm and mixed water)

- Water automatically filled to the exact litre
- Rapid selection of various filling quantities with a  touch panel
- Automatic filling process stop

	○	○	○
--	---	---	---

VAR 808 Core temperature probe

- Cooking to perfection
- Rapid selection of various temperatures with a  touch panel
- Save on energy through optimal cooking time

	○	○	○
--	---	---	---

OPTION

VAR 303 Built-in steam separator	○	○	○
----------------------------------	---	---	---

ACCESSORIES

ZUB F47 Discharge strainer for 60-litre boiling pans	○		
ZUB F48 Discharge strainer for 100-litre boiling pans		○	
ZUB F49 Discharge strainer for 150-litre boiling pans			○
ZUB 320 1 pair of lifting hooks	○	○	○
ZUB 322 Support ring for inserts	○		
ZUB 323 Support ring for inserts		○	
ZUB 324 Support ring for inserts			○
Inserts, 8 mm perforation (up to 2 inserts per appliance)			
ZUB 382 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 384 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 389 1 insert, diameter 675 mm, divided, height 180 mm			○
Inserts, 2.5 mm perforation (up to 2 inserts per appliance)			
ZUB 392 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 394 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 399 1 insert, diameter 675 mm, divided, height 180 mm			○

○ = Optional (price on request)

