

LOW-PRESSURE STEAM TILTING FAST BOILING PANS

- Manual valve for steam feed
- Temperature of the food adjusted manually
- Double-walled lid, spring-released, balanced
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 40 (1 1/2")
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Heating by direct steam supply, 0.3 – 0.5 bar gauge pressure
- Filling level marking with 10-litre graduations
- Continuous cooking mode
- Cleaning-friendly hygiene axles
- Bottom unit as an H2 hygienic model
- Motor tilting function



	FNK 061	FNK 101	FNK 151
Overall dimensions, W × D × H in mm	1000 × 850 × 900	1100 × 850 × 900	1300 × 850 × 900
Weight in kg	164	178	189
Rated output in kW	20.0 at 32 kg/h	29.0 at 46 kg/h	35.0 at 56 kg/h
Electrical connection in kW 230 V 1N 50/60 Hz	0.25	0.25	0.25
Usable capacity in litres	63.5	109	155
Inner pan diameter in mm	484	584	697
Inner pan height in mm	410	470	470
Boiling time, determined to DIN 18855, in minutes (at 0.5 bar gauge pressure)	16	19	21.5
Fast boiling pan according to DIN 18855	●	●	●

STANDARD ACCESSORY

1 strainer	●	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●	●
1 stainless-steel-clad pressure hose for supply of low-pressure steam	●	●	●

OPTION

VAR 303 Built-in steam separator	○	○	○
----------------------------------	---	---	---

ACCESSORIES

ZUB F47 Discharge strainer for 60-litre boiling pans	○		
ZUB F48 Discharge strainer for 100-litre boiling pans		○	
ZUB F49 Discharge strainer for 150-litre boiling pans			○
ZUB 320 1 pair of lifting hooks	○	○	○
ZUB 322 Support ring for inserts	○		
ZUB 323 Support ring for inserts		○	
ZUB 324 Support ring for inserts			○
Inserts, 8 mm perforation (up to 2 inserts per appliance)			
ZUB 382 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 384 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 389 1 insert, diameter 675 mm, divided, height 180 mm			○
Inserts, 2.5 mm perforation (up to 2 inserts per appliance)			
ZUB 392 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 394 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 399 1 insert, diameter 675 mm, divided, height 180 mm			○

○ = Optional (price on request)

