

LOW-PRESSURE STEAM FAST BOILING PANS

- Manual valve for steam feed
- Temperature of the food adjusted manually
- Double-walled lid, spring-released and balanced with all-round seal made of temperature-resistant elastomer
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 40 (1 1/2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Heating by direct steam supply, 0.3 – 0.5 bar gauge pressure
- Filling level marking with 10-litre graduations



	<b>FNS 061</b>	<b>FNS 101</b>	<b>FNS 151</b>
Overall dimensions, W x D x H in mm	700 x 850 x 900	800 x 850 x 900	1000 x 850 x 900
Weight in kg	91	105	122
Rated output in kW	20.0 at 32 kg/h	29.0 at 46 kg/h	35.0 at 56 kg/h
Usable capacity in litres	63.5	109	155
Inner pan diameter in mm	484	584	697
Inner pan height in mm	410	470	470
Boiling time, determined to DIN 18855, in minutes (at 0.5 bar gauge pressure)	16	19	21.5
Fast boiling pan according to DIN 18855	●	●	●

**STANDARD ACCESSORY**

1 strainer	●	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●	●
1 stainless-steel-clad pressure hose for supply of low-pressure steam	●	●	●

**OPTION**

VAR 303 Built-in steam separator	○	○	○
----------------------------------	---	---	---

**ACCESSORIES**

ZUB 320 1 pair of lifting hooks	○	○	○
ZUB 322 Support ring for inserts	○		
ZUB 323 Support ring for inserts		○	
ZUB 324 Support ring for inserts			○

**Inserts, 8 mm perforation (up to 2 inserts per appliance)**

ZUB 382 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 384 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 389 1 insert, diameter 675 mm, divided, height 180 mm			○

**Inserts, 2.5 mm perforation (up to 2 inserts per appliance)**

ZUB 392 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 394 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 399 1 insert, diameter 675 mm, divided, height 180 mm			○

○ = Optional (price on request)