

Salamander Variolift C		Art. No.	Price EUR
Heating with 2 separate controlled HiLight-Heating Systems		954942	
Dimensions (LxDxH)::	600 x 525 / 555 x 456 mm	Sensible heat emission:	2,80 kW
Connected Load:	4,6 kW 400 V 2 N 50/60 Hz	Latent heat emission:	0,70 kW
		Steam emission:	1,03 kg / h

- Equipped on three sides and adjustable in height on three sides
- Infinitely variable from 73 to 210 mm
- Surrounding red handle (temperature <60°C)
- Manual or automatical operation with mechanical timer and plate recognition
- 4 heating stages: full / right / left / keep warm

Capacity: 1x GN 1/1 or 2 plates Ø 300 mm



Salamander Variolift C		Art. No.	Price EUR
Heating with 2 separate controlled HiLight-Heating Systems		878381	
Dimensions (LxDxH)::	600 x 525 / 555 x 456 mm	Sensible heat emission:	2,80 kW
Connected Load:	4,6 kW 400 V 2 N 50/60 Hz	Latent heat emission:	0,70 kW
		Steam emission:	1,03 kg / h

Special features:

- Surrounding black handle (temperature <60°C)

Other characteristics like Salamander Variolift C / Art. No. 954942



Salamander Variolift C-BE (Black Edition)		Art. No.	Price EUR
Heating with 2 separate controlled HiLight-Heating Systems		887352	
Dimensions (LxDxH)::	600 x 525 / 555 x 456 mm	Sensible heat emission:	2,80 kW
Connected Load:	4,6 kW 400 V 2 N 50/60 Hz	Latent heat emission:	0,70 kW
		Steam emission:	1,03 kg / h

Special features:

- Surrounding black handle (temperature <60°C)
- Black operating panel

Other characteristics like Salamander Variolift C / Art. No. 954942



Salamander Variolift C Plus		Art. No.	Price EUR
Heating with 2 separate controlled HiLight-Heating Systems		956813	
Dimensions (LxDxH):	600 x 525 / 555 x 456 mm	Sensible heat emission:	2,80 kW
Connected Load:	4,6 kW 400 V 2 N 50/60 Hz	Latent heat emission:	0,70 kW
		Steam emission:	1,03 kg / h

- Equipped on three sides and adjustable in height on three sides
- Infinitely variable from 73 to 210 mm
- Manual or automatic operation with electronic timer from 0-20 minutes
- Operation via selector switch and panel buttons
- Automatic cut off with acoustic signal
- Surrounding red handle (temperature <60°C)
- Timer memory function and plate recognition
- 4 heating stages: full / right / left / keep warm



Capacity: 1x GN 1/1 or 2 plates Ø 300 mm




Salamander Variolift C Plus - BE (Black Edition)		Art. No.	Price EUR
Heating with 2 separate controlled HiLight-Heating Systems		887353	
Dimensions (LxDxH):	600 x 525 / 555 x 456 mm	Sensible heat emission:	2,80 kW
Connected Load:	4,6 kW 400 V 2 N 50/60 Hz	Latent heat emission:	0,70 kW
		Steam emission:	1,03 kg / h

Special features:

- Surrounding black handle (temperature <60°C)
- Black operating panel

Other characteristics like Salamander Variolift C Plus / Art. No. 956813



Accessories Salamander Variolift C and Variolift C Plus		Art. No.	Price EUR
Ceiling mounting kit Maximum height 2.000 mm		SA373162	
Hood mounting kit, lengthwise		SA373163	
Hood mounting kit, crosswise		SA373164	
Wall installation set Dimensions: 406 x 125 x 34 mm		SA373208	
Table top rack Dimensions: 470 x 443 x 200 mm		SA373209	
Assembly heat protecting guard - for Salamander above thermal components Dimensions: 474 x 468 x 2,5 mm		SA373159	
Supporting frame - for Salamander on heating bridges Dimensions: 475 x 445 x 13 mm		878664	

All indicated prices are net prices and are valid for a delivery within 6 weeks after placement of the order. If delivery has to be made later than 6 weeks after placement of the order, the prices will be adjusted according to the then valid price-list. All prices are per item. Our terms of delivery are: EXW Bad Mergentheim (according to Incoterms 2010), packing for land transport included, excluding vat. The prices mentioned in this price-list do not include installation of the appliances.

All listed values are middle values and refer to normal operation. Calculated in accordance with VDI2052 04/2006.

Subject to changes in power, dimensions and construction.



PALUX Aktiengesellschaft
 Wilhelm-Frank-Straße 36
 97980 Bad Mergentheim
 GERMANY
 Telephone: +49 7931 55 0
 Telefax: +49 7931 55 88600
 Internet: www.palux.de
 E-Mail: info@palux.de
 Art. No. 700169 / 01.01.2023

PALUX

Das gute Fröhen